

TP500



Two Stage Pedestal

The Shotoku TP500 is a compact, lightweight, portable pneumatic pedestal capable of supporting payloads of up to 55 kg (121.2lbs). Suitable for OB, studio, or event production, the robust modular design makes transportation between locations simple with no compromise in stability or quality of operation.

Unique to the TP500 is an integrated inflation pump which offers owners freedom and peace-of-mind knowing their pedestal will be perfectly balanced regardless the location. With a wide stroke, column drag and lock functions, and folding dolly with and track lock, the TP500 is the perfect solution for users whose priority is versatility.



Combine with SX300 head



TZ-63 100mm ball adaptor

MAX. PAYLOAD	55kg / 121.2lbs
MAX. HEIGHT	1,485mm / 58.5"
MIN. HEIGHT	670mm / 26.4"
OVERALL STROKE	815mm / 32.1"
ON-SHOT STROKE	405mm / 15.9"
TRACKING WIDTH	950mm / 37.4"
TRANSIT WIDTH	860mm / 33.9"
WEIGHT	27kg / 59.5lbs
GROUND CLEARANCE	20mm / 0.8"
WHEEL DIAMETER	125mm / 5"
STEERING RING DIAMETER	535mm / 21.1"
INDIVIDUAL TRIM WEIGHT (x6)	0.5kg / 1.2lbs
MOUNT	4-Bolt Flat Base
SUITABLE HEAD	SX300, SX260, SX200



Detachable column unit

Integrated pump for pressure adjustments on location

Column drag and lock functions for extra control and security

Two stage (1+1) perfect balance pneumatic upper plus gas strut assisted manually positioned lower, enabling the capture of a wide range of shots

Detach and fold the dolly for compact storage and easy transport to remote locations

